

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau




(43) International Publication Date
5 February 2004 (05.02.2004)

PCT

(10) International Publication Number
WO 2004/011828 A1

- (51) International Patent Classification⁷: F16J 15/32 (74) Agent: OY JALO ANT-WUORINEN AB; Iso Roobertinkatu 4-6 A, FIN-00120 Helsinki (FI).
- (21) International Application Number: PCT/FI2003/000556 (81) Designated States (*national*): AU, BR, BY, CA, CN, IN, JP, KR, LT, LV, MX, NO, PL, RU, SG, UA, US, ZA.
- (22) International Filing Date: 9 July 2003 (09.07.2003) (84) Designated States (*regional*): European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR).
- (25) Filing Language: Finnish (26) Publication Language: English
- (30) Priority Data: 20021414 26 July 2002 (26.07.2002) FI Published: — with international search report
- (71) Applicant and (72) Inventor: LEHTINEN, Reijo [FI/FI]; Rantakatu 51 A 36, FIN-92101 Raahе (FI). For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A SEAL STRUCTURE FOR SEALING THE INLET/EXIT PASSAGEWAY OF AN ELONGATED OBJECT



(57) Abstract: The invention relates to a seal structure for sealing the inlet/exit gate passageway of an elongated object (1) from a process cavity (A, B) or into such a cavity. The seal structure comprises sheet-metal structures, which essentially delineate the passageway and are removably mounted on the frame structure (3) of said process cavity, and a sweeping seal element (13) enclosing the passageway. The sheet-metal element structures comprise at least two sheet-metal elements (14, 15, 15x) that have a shape taperingly departing from the frame structure (3) of the process cavity so as to be inclined in the nominal travel direction of the object (1) and are kept compressed mutually against each other so as to hold a seal element (13, 13x) therebetween.

WO 2004/011828 A1